

# LWFix 深圳市励维科技有限公司

Shenzhen Liwei Technology Co., Ltd.

Add: 3rd Floor, Building 1, Wananshun Industrial Park, No. 210 Wanfeng Middle Road, Xinqiao Street, Shenzhen, Guangdong, China

## 一、LV-08s BGA Rework station picture.



## 二、LV-08s BGA Rework station introduction:

- Independent three-temperature zone temperature control system:

① Upper and lower temperature zone both are hot air heating, IR preheating zone for bright infrared heating, the temperature is accurately controlled at  $\pm 2$  °C, the upper and lower temperature zone can be heated from the top of the components and the bottom of the PCB at the same time, meanwhile can be set up to 8 temperature control, so that the PCB board is heated uniformly, the bottom are the large IR preheating, so that

the entire PCB temperature, to prevent deformation, to ensure that the welding effect, the heating plate can be independently controlled by the heating.

② BGA chips and PCB boards can be hot air local heating at the same time, supplemented by a large area of infrared heaters on the bottom of the PCB board for preheating, can completely avoid the deformation of the PCB board in the rework process; through the selection of the upper temperature zone can be used individually or the lower temperature zone, and the free combination of upper and lower heaters Energy.

③ Select high-precision K-type thermocouple closed-loop control and PID parameter self-tuning system; can simultaneously display four temperature curves and store multiple sets of user data, and has an instantaneous curve analysis function; external temperature measurement interface to achieve precision detection of the temperature, can be analyzed and calibrated at any time on the actual acquisition of the BGA temperature curve. It can also analyze, set and correct the curve of temperature parameters on the touch screen at any time.;

- Precise Optical Alignment System: Adopting high-definition adjustable CCD color optical vision alignment system with beam splitting, zoom-in, zoom-out, and auto focus functions, and equipped with automatic chromatic aberration resolution and brightness adjustment device, which can adjust the clarity of the image; equipped with a 15" high-definition LCD monitor.

- Versatile and user-friendly operating system

① Adopting high-definition touch screen man-machine interface, upper heating device and mounting head integrated design. Equipped with a variety of specifications of titanium alloy BGA nozzle, the nozzle can be rotated 360 ° arbitrary, easy to install and replacement.

② The X and Y axes and the R angle are fine-tuned using micrometers for precise alignment and accuracy up to  $\pm 0.01$  mm.

- Superior Features:

① With 4 operating modes, Four modes: remove, weld, mounting, semi-auto.

② Percentage air speed adjustment, fan speed and chip temperature profile saved at the same time.

③ Slide rails drive the upper heating head, more precision.

### 三、LV-08s technical parameters

Total power	5400W
Upper heating power	1200W

Lower heating power	1200W
Lower heating power	2800W (1400W control)
Power supply	(Single Phase) AC 220V±10 50Hz
Positioning method	V-slot + universal fixture + laser positioning light for quick positioning
Temperature control	High-precision K-type thermocouple (Ksensor) closed loop control (Closed Loop), the upper and lower independent temperature measurement ( $\pm 2$ degree);
Electrical Selection	Highly sensitive touch screen+micro controller+stepper drive
Max PCB size	560×380mm
Min PCB size	10×10mm
Temperature sensor	3pcs
Chip magnification	1-200 times
PCB thickness	0.5-8mm
Applicable chips	0.8mm-6cm
Minimum chip pitch	0.15mm
Maximum load for mounting	100G
Mounting accuracy	$\pm 0.01$ mm
Overall dimensions	L760×W640×H870mm
Machine weight	About 75kg